

350 mm Ø

4-6 POLES/POLOS



Dimensions and Construction Dimensiones y Construcción

Airflow
B ←

Characteristics / Características

4-350 1~ 230V 50Hz

CAP = 8 uF Is/In = 2,8

Type / Tipo	Curve Curva	Voltage Tensión (V)	Point Punto	I (A)	P (W)	N (rpm)	LwA dB (A)	Tmax. (°C)
HRB/4-350	1	230	L	0,63	128	1392	69	
	1	230	M	0,65	131	1356	65	
	1	230	H	0,69	134	1306	70	55

4-350 3~ 230/400V 50Hz

Is/In = 2,7

Type / Tipo	Curve Curva	Voltage Tensión (V)	Point Punto	I (A)	P (W)	N (rpm)	LwA dB (A)	Tmax. (°C)
HRT/4-350	2	230/400	L	0,61/0,35	131	1397	69	
	2	230/400	M	0,65/0,38	135	1369	65	
	2	230/400	H	0,70/0,40	141	1331	70	55



6-350 1~ 230V 50Hz

CAP = 2 uF Is/In = 2,9



Type / Tipo	Curve Curva	Voltage Tensión (V)	Point Punto	I (A)	P (W)	N (rpm)	LwA dB (A)	Tmax. (°C)
HRB/6-350	3	230	L	0,28	67	890	59	
	3	230	M	0,28	68	878	55	
	3	230	H	0,29	70	852	60	50

Weight/Peso (Kg)


Type / Tipo	S	PN	Q	Z
HRB/4-350	4	5	5	7
HRT/4-350	4	5	5	7
HRB/6-350	4	5	5	7





S



PN



Q



Z

