

400 mm Ø

4-6 POLES/POLOS



Dimensions and Construction Dimensiones y Construcción

Airflow
B ←

Characteristics / Características

4-400 1~ 230V 50Hz

CAP = 4 uF Is/In = 2,9

Type / Tipo	Curve Curva	Voltage Tensión (V)	Point Punto	I (A)	P (W)	N (rpm)	LwA dB (A)	Tmax. (°C)
HRB/4-400	1	230	L	0,71	126	1150	68	
	1	230	M	0,73	130	1130	66	
	1	230	H	0,75	134	1120	66	55

4-400 3~ 230/400V 50Hz

Is/In = 2,9

Type / Tipo	Curve Curva	Voltage Tensión (V)	Point Punto	I (A)	P (W)	N (rpm)	LwA dB (A)	Tmax. (°C)
HRT/4-400	2	230/400	L	0,66/0,39	133	1250	68	
	2	230/400	M	0,68/0,39	135	1160	66	
	2	230/400	H	0,71/0,41	140	1077	66	55



6-400 1~ 230V 50Hz

CAP = 2 uF Is/In = 2,9



Type / Tipo	Curve Curva	Voltage Tensión (V)	Point Punto	I (A)	P (W)	N (rpm)	LwA dB (A)	Tmax. (°C)
HRB/6-400	3	230	L	0,26	59,5	789	60	
	3	230	M	0,27	62,8	722	56	
	3	230	H	0,28	65	607	54	60

Weight/Peso (Kg)




Type / Tipo	S	PN	Q	Z
HRB/4-400	5	6	6	8
HRT/4-400	5	6	6	8
HRB/6-400	5	6	6	8






S



PN



Q



Z

