

RZM 13-1250

Technical Data

RZM 13-	Nominal motor power kW	Poles	Motor size	Motor voltage V	Phases	Nominal frequency Hz	Connection	Nominal motor current A	Nominal motor speed 1/min	Max. fan speed 1/min	Max. operating frequency Hz	Weight kg
1250-8D-42	45	8	280M	400	3~	50	△	87	735	740	50	2115
1250-8D-44	55	8	315S	400	3~	50	△	106	740	790	53	2255
1250-8D-46	75	8	315M	400	3~	50	△	140	738	880	59	2370
1250-8D-50	90	8	315L	400	3~	50	△	168	738	935	63	2510
1250-6W-50	110	6	315L	400	3~	50	△	196	988	990	50	2490
1250-6W-51	132	6	315L	400	3~	50	△	235	988	1055	53	2580

Motor code:

- W = Asynchronous motor (efficiency class IE2)
- D = Asynchronous motor

Dimensions in mm, subject to change.

Motor	G	k2
280	3096	-
315	3272	127

Accessories

RZM 13-	Frequency inverter 6SE6430-	Control Panel for frequency inverter 6SE6420- and 6SE6430-	Line Choke for 3~	Interference Suppression Filter - Class A
1250-8D-42	6SE6430-2AD35-5FA0	6SE6400-0BE00-0AA0	6SE6400-3CC11-2FD0	-
1250-8D-44	6SE6430-2AD37-5FA0	6SE6400-0BE00-0AA0	6SE6400-3CC11-2FD0	-
1250-8D-46	6SE6430-2AD38-8FA0	6SE6400-0BE00-0AA0	6SE6400-3CC11-7FD0	-
1250-8D-50	6SE6430-2AD38-8FA0	6SE6400-0BE00-0AA0	6SE6400-3CC11-7FD0	-
1250-6W-50	6SE6430-2UD41-3FA0	6SE6400-0BE00-0AA0	6SL3000-OCE32-8AA0	6SL3000-0BE34-4AA0
1250-6W-51	6SE6430-2UD41-3FA0	6SE6400-0BE00-0AA0	6SL3000-OCE32-8AA0	6SL3000-0BE34-4AA0